

Vidi-Touch Navigator

84 Inch 4K

Design	Distributed By	Vidstri Europe
	Origin	South Korea
	Frame Material	AL Anodizing
	Frame Color	Black-standard, Silver, Wine, Olive Gold
	Frame Design	Round corner
	Glass Type	Black coated AG++
	Glass Thickness	5mm
Interactive touch	Touch Screen Size	90 inch (229cm)
	Precision Touch Technology	DOW IR (Optical camera + IR)
	Touch Point	10 touch points
	Touch Tool	Finger/Stylus
	Fastkey	Hardware Fastkey
	Response Time	< 7ms
	Interface	USB 1.1, HID compliant, Plug & Play, USB 2.0
	Supported OS	WinXP, Vista,7,8,10, Mac OSX, Android, Linux
	Driverless	Support
	Display	Type
Panel Diagonal Size		84 inch (213cm)
Panel Resolution		3840 x 2160 Ultra HD
Recommand Resolution		3840x2160 @ 60Hz
Brightness (nits)		350cd/m2
Contrast ratio		1600:1
Response Time		5 (typ.) (G to G), 8 (typ.) (MPRT)
Aspect ratio		16:9
Display Color		16.7M/1.06B (8-bit/8-bit+dithering)
Viewing Angle		178'
Pixel Pitch (mm)		0.485 x 0.485 mm
Color Gamut		72% NTSC
W x H (mm)		1860.48 x 1046.52 mm
Life Time (hrs)		50,000
Panel Maker		LGD
Audio	Internal SPK	2x 15W
	SPK Out	2x 15W

Connectivity	Video Input	4x HDMI, VGA, USB Component
	Audio Input	3.5 Stereo, RCA L/R
	Audio Output	SPK output, Earphone, SPDIF
	USB for Touch	2x USB automatic switch
	Control	RS-232
OSD Convenient	Video PSM	Standard/Dynamic/Theater/Personal
	Video Picture Mode	Brightness/Contrast/Color/Sharpness
	Color Status Memory	Normal/Warm/Cool
	Sound stereo	MTS (Stereo / Mono)
	Sound SSM	Standard/Music/Movie/Sports/Personal
	Sound Equalizer	2 band
	Sound Output	15W 2CH RMS
Storage & Operating	OSD Language	English / Spanish / French
	Storage Temperature	- 20 ~ 60°C
	Operating Temperature	5 ~ 35°C
	Storage Humidity	5-90% RH
	Operating Humidity	20-80%
	Noise	Below 40dB @25C
Accessories	HDMI Cable	Yes
	USB & Extension Cables	Yes
	Power Cable	Yes
	Stylus Pen	Yes
	Remote controller	Yes
	User Manual	Yes
Power	Cleaning Cloth	Yes
	Power Requirements	100 to 240V AC, 50/60Hz
	Power Consumption Max.	470W
Dimensions	Power Consumption Typ.	430W
	Product Dimensions (mm)	2237 x 1234 x 117
	Weight (kg)	124
	Packing dimensions (mm)	2370 x 360 x 1370
	Packing weight (Kg)	163
Bracket Mount	600 x 400	