



	65 inch	75 inch	86 inch
BACKLIGHT		LED	
DISPLAY AREA	1428.5 x 803.5mm	1650 x 973mm	1895.04 x 1065.96 mm
ACTIVE SCREEN SIZE	65 inch	75 inch	86 inch
DISPLAY RATIO		16:9	
RESOLUTION		3840 x 2160 Pixels	
DISPLAY COLORS		10-bit	
BRIGHTNESS		370nit	
CONTRAST		4000:1	
RESPONSE TIME		8ms	
VIEWING ANGLE		178°	
SPEAKER POSITION		Forward	
POWER CONSUMPTION	Maximum <220W Standby Mode ≤0.5W	Maximum < 300W Standby Mode ≤0.5W	Maximum <450W Standby Mode ≤0.5W
WORKING VOLTAGE		AC 100-240V, 50/60Hz	
TOUCH SURFACE	Optical Bonding Anti-Glare & Anti-Finger Print Glass		
TRANSPARENCY		88%	
SURFACE HARDNESS		7H	
TOUCH POINTS		Up to 20 points Touch	
WRITING TOOLS		Stylus or finger	
COMMUNICATION INTERFACE		USB-A	
STORAGE TEMP./ HUMIDITY		-20°C-60°C/ 20 - 80%	
WORKING TEMP./ HUMIDITY		0°C-40°C/ 20 - 80%	
MOUNTING (optional)		Wall-mounted / Floor Stand	
OUTLINE DIMENSION	1546 x 944 x 89 mm	1771 x 1071 x 108 mm	2018 x 1211 x 104 mm
NET WEIGHT	39 ± 1KG	51 ± 1KG	65 ± 1.5KG
INTERFACE INPUT FRONT	HDMI x1, USB (Touch) x 1, DYNAMIC USB x 2		
AV INPUT	HDMI x 3, DP x 1, USB (Touch) x 4		
AV OUTPUT	HDMI x 1, Line Out x 1, DC Out (5V 3A) for X10D		
OTHER	DYNAMIC USB 2.0 x 2, RS232 x 1, RJ45 x 2, DYNAMIC USB 3.0 x 1, OPS Slot		
WIRELESS PRESENTATION	MONTAGE for WINDOWS Included / TRUCAST (Optional)		
INTELLIGENT THERMO PROTECTOR		YES	
BUILT-IN WI-FI		2.4G/5G	


Front Interface Inputs



AV Inputs / Outputs



Other



Distributor:

Vidistri Europe B.V.
Middellaan 8c 6881 RP
Velp The Netherlands

More information:

+31(0) 26 36 18 232
verkoop@vidistri.nl
www.viditouch.eu