

55 inch

Design	DISTRIBUTED BY	Vidistri Europe	VIDEO INPUT	3x HDMI, VGA,	Connectivity	
	ORIGIN	South Korea		USB Component		
	FRAME MATERIAL	AL Anodizing	USD FOR TOUCH	2x USB automatic switch		
	FRAME COLOR	Black-standard	CONTROL	RS-232		
	FRAME DESIGN	Round corner				
	GLASS TYPE	Black coated AG++	VIDEO PMS	Standard/Dynamic/Theater/Personal		
	GLASS THICKNESS	4mm	VIDEO PICTURE MODE	Brightness/Contrast/Color/Sharpness		
Interactive touch	TOUCH SCREEN SIZE	60 inch (152 cm)	COLOR STATUS MEMORY	Normal/Warm/Cool	OSD Convenient	
	PRECISION TOUCH TECHNOLOGY	DOW IR (Optical camera + IR)	SOUND STEREO	MTS (Stereo / Mono)		
	TOUCH POINT	4/10 touch points	SOUND SSM	Standard/Music/Movie/Sports/Personal		
	TOUCH TOOL	Finger/Stylus	SOUND EQUALIZER	2 band		
	FASTKEY	Hardware Fastkey	SOUND OUTPUT	15W 2CH RMS		
	RESPONSE TIME	<7 ms	OSD LANGUAGE	English/Spanish/French		
	INTERFACE	USB 1.1, HID compliant, Plug & Play, USB 2.0				
	SUPPORTED OS	WinXP, Vista, 7, 8, 10, Android, Linux	STORAGE TEMPERATURE	-20 ~ 60°C		Storage & Operating
	DRIVERLESS	Support	OPERATING TEMPERATURE	5 ~ 35 °C		
			STORAGE HUMIDITY	5-90% RH		
		OPERATING HUMIDITY	20~80%			
Display	TYPE	LCD (LED Backlight) Panel	NOISE	Below 40dB @25°C	Accessories	
	PANEL DIAGONAL SIZE	55 inch (139 cm)	HDMI CABLE	Yes		
	PANEL RESOLUTION	1920 x 1080	USB & EXTENSION CABLES	Yes		
	PANEL RESOLUTION	1920 x 1080	POWER CABLE	Yes		
	BRIGHTNESS (NITS)	350cd/m2	STYLUS PEN	Yes		
	CONTRAST RATIO	1400:1	REMOTE CONTROLLER	Yes		
	RESPONSE TIME	6 (typ) (G to G), 8 (typ) (MPRT)	USER MANUAL	Yes		
	ASPECT RATIO	16:9	CLEANING CLOTH	Yes		
	DISPLAY COLOR	16.7M				
	VIEWING ANGLE	178'	POWER REQUIREMENTS	100 to 240V AC, 50/60Hz		Power
PIXEL PITCH (MM)	0.630 x 0.630 mm	POWER CONSUMPTION MAX	150W			
COLOR GAMUT	68	POWER CONSUMPTION TYP.	120W			
W X H (MM)	1244.46 x 720.4					
Audio	LIFE TIME (HRS)	50,000	PRODUCT DIMENSIONS (MM)	1552 x 860 x 100	Dimension	
	PANEL MAKER	LGD	WEIGHT (KG)	56		
			PACKING DIMENSIONS (MM)	1620 x 270 x 960		
	INTERNAL SPK	15W x 2	PACKING WEIGHT (KG)	73		
	SPK OUT	15W x 2	BRACKET MOUNT	400 x 400		
AUDIO INPUT	3.5 Stereo, RCA L/R					
AUDIO OUTPUT	SPK output, Earphone, SPDIF					

**Distributor:**

Vidistri Europe B.V.  
Middellaan 8c 6881 RP  
Velp The Netherlands

**More information:**

+31(0) 26 36 18 232  
verkoop@vidistri.nl  
www.viditouch.eu