

## 65 inch 4K

Design	DISTRIBUTED BY	Vidistri Europe	VIDEO INPUT	4x HDMI, VGA, USB Component		
	ORIGIN	South Korea				
	FRAME MATERIAL	AL Anodizing, Black Coated	USD FOR TOUCH	USB		
		Acrylic	CONTROL	RS-232		
	FRAME COLOR	Black-standard				
	FRAME DESIGN	Round corner	VIDEO PMS	Standard/Dynamic/Soft/User		
	GLASS TYPE	Black coated AG++	VIDEO PICTURE MODE	Brightness/Contrast/Color/Sharpness		
GLASS THICKNESS	4mm					
			COLOR STATUS MEMORY	Normal/Warm/Cool		
Interactive touch	TOUCH SCREEN SIZE	70 inch (178cm)	SOUND STEREO	MTS (Stereo / Mono)		
	PRECISION TOUCH TECHNOLOGY	DOW IR (Optical camera + IR)	SOUND SSM	Standard/Dynamic/Soft/User		
	TOUCH POINT	10 touch points	SOUND EQUALIZER	2 band		
	TOUCH TOOL	Finger/Stylus	SOUND OUTPUT	15W 2CH RMS		
	FASTKEY	Hardware Fastkey	OSD LANGUAGE	English/Spanish/French		
	RESPONSE TIME	<7 ms				
	INTERFACE	USB 1.1, HID compliant,	STORAGE TEMPERTURE	-20 ~ 60°C		
		Plug & Play, USB 2.0	OPERATING TEMPERATURE	5 ~ 35 °C		
	SUPPORTED OS	WinXP, Vista, 7, 8, 10,	STORAGE HUMIDITY	5-90% RH		
		Android, Linux	OPERATING HUMIDITY	20~80%		
DRIVERLESS	Support	NOISE	Below 40dB @25°C			
Display	TYPE	LCD (LED Backlight) Panel	HDMI CABLE	Yes		
	PANEL DIAGONAL SIZE	65 inch (164 cm)	USB & EXTENSION CABLES	Yes		
	PANEL RESOLUTION	3840 x 2160 Ultra HD	POWER CABLE	Yes		
	BRIGHTNESS (NITS)	450cd/m2	STYLUS PEN	Yes		
	CONTRAST RATIO	1400:1	REMOTE CONTROLLER	Yes		
	RESPONSE TIME	6 (typ) (G to G), 8 (typ) (MPRT)	USER MANUAL	Yes		
	ASPECT RATIO	16:9	CLEANING CLOTH	Yes		
	DISPLAY COLOR	16.7M/1.06B (8-bit/				
		8-bit+dithering)	POWER REQUIREMENTS	100 to 240V AC, 50/60Hz		
	VIEWING ANGLE	178'	POWER CONSUMPTION MAX	180W		
PIXEL PITCH (MM)	0.372 x 0.372 mm	POWER CONSUMPTION TYP.	150W			
COLOR GAMUT	72% NTSC					
W X H (MM)	1428.48 x 803.52 mm	PRODUCT DIMENSIONS (MM)	1770 x 982 x132			
LIFE TIME (HRS)	50,000	WEIGHT (KG)	79			
PANEL MAKER	LGD	PACKING DIMENSIONS (MM)	1880 x 310 x 1100			
		PACKING WEIGHT (KG)	103			
Audio	INTERNAL SPK	High End	BRACKET MOUNT	456x 400		
	SPK OUT	15W x 2				
	AUDIO INPUT	3.5 Stereo, RCA L/R				
	AUDIO OUTPUT	SPK output, Earphone, SPDIF				

**Distributor:**

Vidistri Europe B.V.  
Middellaan 8c 6881 RP  
Velp The Netherlands

**More information:**

+31(0) 26 36 18 232  
verkoop@vidistri.nl  
www.viditouch.eu